



HD53EA010

HIGH DENSITY POLYETHYLENE FOR STRETCHED TAPE PRODUCTS

HD53EA010 is a High Density Polyethylene (HDPE) grade produced and specially formulated to manufacture stretched tape products and other extrusion products with good combination of tenacity and elongation. It has very good processability and stretchability, less motor load and high output combined with good tape properties to make it a grade of choice.

| Typical Characteristics* | | | |
|---------------------------------|-------------|--------------------|-----------------|
| Property | Test Method | Unit | Typical Value** |
| Melt Flow Index (190°C/2.16 kg) | ASTM D1238 | gm/10 min | 1.0 |
| Density (23°C) | ASTM D1505 | gm/cm ³ | 0.955 |
| Tensile Strength at Yield | ASTM D638 | MPa | 23 |
| Elongation at Break | ASTM D638 | % | 15 |
| Flexural Modulus | ASTM D790 | MPa | 820 |
| Notched Izod Impact Strength | ASTM D256 | J/m | No Break |
| Vicat Softening Point | ASTM D1525 | °C | 127 |

*Typical Characteristics and not to be taken as specifications

**Mechanical Properties are on Injection Moulded Specimen

Applications

Oriented tapes, woven sacks.

Regulatory Information

- Meets the requirements stipulated in standard IS : 10146-1982 on "Specification for Polyethylene for safe use in contact with foodstuffs, pharmaceuticals, and drinking water". It also conforms to the positive list of constituents as prescribed in IS : 10141-1982. The grade and the additives incorporated in it also comply with the FDA:CFR Title 21, 177.1520, Olefin polymers.

Storage Recommendations

- Bags should be stored in dry / closed conditions at temperatures below 50°C and protected from UV / direct sunlight.